

THE NEW SYLVAC BLUETOOTH® ULTRALIGHT CALIPER SERIE 4

The new ultralight caliper **UL4**, new design, new features, built-in Bluetooth transmitter: Discover our amazing new ultra-light long range calipers



UL4 Bluetooth®

- Built-in Bluetooth® 4.0
- New reinforced frame
- **XXL display with 20 mm high digits**
- Increased accuracy
- **Lengthened jaws 200 mm**
- New system for internal measurement
- **Protected IP67**

 UL4 Bluetooth®



TECHNICAL SPECIFICATIONS

Specifications	811.1404	811.1406	811.1410	811.1415	811.1420	811.1425	811.1430
Measuring range	400 mm	600 mm	1000 mm	1500 mm	2000 mm	2500 mm	3000 mm
Max error ¹⁾	30 µm	40 µm	50 µm	90 µm	120 µm	150 µm	200 µm
Repeatability ²⁾	20 µm				30 µm		
Measuring force	7.5 – 11.5 N (±20%)						
Connection	Bluetooth® Smart * / Proxi.–RS232 or – USB						
Protection rating	IP67 (electronic module)						
Preset max.	± 9999.99 mm / ± 399.9995 IN						
Weight	1.5 kg	1.6 kg	1.9 kg	2.3 kg	2.6 kg	2.9 kg	3.3 kg

¹⁾ According to DIN 863

²⁾ ± digit

* More informations on How to use Bluetooth® leaflet SYL_1401_EN_BT